

Bona Sportive Finish





Bona Sportive Finish

Bona Sportive Finish is a 2-component waterborne 100% polyurethane finish for the surface treatment of wooden sports floors in both specialist and multipurpose environments.



Key Benefits

- 100% polyurethane
- High resistance to wear, scuff marks and scratches
- Very good chemical resistance
- Meets DIN norm 18 032:2 for slip resistance

Technical Data

Type of finish: 2-component waterborne 100%

polyurethane finish

Solids content: Approx. 32%

Viscosity: Approx. 17 sec. (25°C, FC4)

pH-value: Approx. 8

Resistance to wear: Approx. 5 mg/100 revolutions (SIS

923509)

Sheen (at 60°): Gloss: approx. 90,

Matt: approx. 20

Mixing ratio: 4% Bona Sportive Hardener

(40 ml: 1 litre finish)

Drying time: 2½ – 3 hours at 20°C/60% R.H.

Application tools: Bona Roller or Bona Applicator Bar

Application rate: 8–10 m²/litre (120–100g/m²) per coat

Safety: Finish: Unclassified

Hardener: Classified (see Safety Data Sheet)
Shelf life: 1 year, from date of production, in

unopened original container

Storage/transport: The temperature must not fall below

+5°C or exceed +25°C during stor-

age and transport

Disposal: Wastes and emptied containers

should be handled in accordance with

local regulations.

Pack size: 2 x 10 litres + 2 x Sportive Hardener

(24 boxes per pallet)

